



ENERGY STAR CERTIFIED

Uninterruptible Power Supplies

EATON - 5PX3000iRT3UAU : 5PX3000iRT3UAU

Specifications

| | |
|--|-----------------------------------|
| Brand Name: | EATON |
| Model Name: | 5PX3000iRT3UAU |
| Model Number: | 5PX3000iRT3UAU |
| Power Conversion Mechanism: | Static |
| Minimum Configuration Tested Model Number: | 5PX3000iRT2U |
| Active Output Power Rating Minimum Configuration (W): | 2700 |
| Apparent Output Power Rating Minimum Configuration (VA): | 3000 |
| Topology (ac): | Line Interactive |
| Topology and Product Type Combined: | ac Line Interactive (VI) |
| Application: | Commercial |
| Rated Input Voltage (V rms): | 200-240 |
| Rated Input Frequency (Hz): | 50-60 |
| Rated Output Voltage (V): | 200-240 |
| Rated Output Frequency (Hz): | 50-60 |
| Rack Mountable: | Yes |
| Rack Mount Height (U): | 3 |
| Height (mm): | 131 |
| Width (mm): | 441 |
| Depth (mm): | 497 |
| Total Number of Outlets: | 9 |
| Normal Mode(s) Input Dependency Characteristic (ac): | Voltage Independent |
| Modular UPS: | No |
| Number of Normal Modes: | Single-normal-mode |
| Default Normal Mode (ac): | Voltage and Frequency Independent |
| Test Input Voltage (V rms): | 230 |
| Test Input Frequency (Hz): | 50 |
| Test Output Voltage (V): | 230 |
| Test Output Frequency (Hz): | 50 |
| Total Input Power in W at 0% Load Min Config Lowest Dependency (ac): | 0.214 |

| | |
|--|---|
| Efficiency at 25% Load Min Config Lowest Dependency (ac): | 96.9 |
| Efficiency at 50% Load Min Config Lowest Dependency (ac): | 98.1 |
| Efficiency at 75% Load Min Config Lowest Dependency (ac): | 98.5 |
| Efficiency at 100% Load Min Config Lowest Dependency (ac): | 98.6 |
| Weighted Efficiency Calc Min Config Lowest Dependency: | 98.4 |
| Efficiency (%): | 98.4 |
| Modular UPS Module Tested Model Number: | N/A |
| Energy Storage Mechanism: | Battery |
| Energy Storage System Technology: | Valve Regulated Lead-acid Battery |
| Energy Storage System Configuration: | Integral |
| Energy Storage System Removable to Another Room: | No |
| Energy Storage System Runtime at 100% Load (min.): | 3 |
| Energy Storage System Runtime at 50% Load (min.): | 10 |
| Energy Storage System Warranty (yrs): | 3 |
| Energy Storage System Information URL: | N/A |
| Network Connections Available: | Serial Port,USB Port,Ethernet |
| Communication Protocols: | HTTP,HTTPS,SNMP (v1, 2 or 3) |
| Manufacturer Take Back Program: | No |
| Model Web Page URL: | http://powerquality.eaton.com/5PX3000iRT3UAU.aspx?cx=22 |
| Test Method Guidelines: | N/A |
| Date Available on Market: | 2018-12-11 |
| Date Certified: | 2018-12-11 |
| Markets: | United States, Switzerland, Taiwan, Japan, Canada |
| ENERGY STAR Certified: | Yes |

Additional Model Information

Captured On:
04/08/2021